

APPLICATION NOTE 163

Digital Hall Sensors

Introduction

Hall based sensors are a widely used sensor system that provides the rotor position feedback to the motor controller. All FAULHABER BLDC motors have integrated digital hall sensors as the standard version. Digital hall sensors are used for the trapezoidal commutation for the speed control applications. The digital hall sensors are in general very economical, compact and ease to use with speed controllers.

Related products

2-Pole Motors	4-Pole BX4 Motors	4-Pole BP4 Motors	4-Pole Flat Motors	7-Pole Flat Motors
0620...B	2232...BX4 (S)	2264...BP4	1509...B	2214...BXT
0824...B	2250...BX4 (S)	3274...BP4	1515...B	3216...BXT
1028...B	3242...BX4		2610...B	4221...BXT
1218...B	3268...BX4		2622...B	
1226...B				
1628...B				
1645...B				
1660...B				
2036...B				
2057...B(HS)				
2444...B				
3056...B				
3564...B				
4490...B(S)				

Table 1 Motors that can be equipped with digital hall sensors

Glossary

There are a few special terms in this product application note:

Table 2 FAULHABER Motion Controllers and Speed Controllers supporting digital hall-sensors

120°e	The °e denotes an electrical angle of a motor. Here we are mostly discussing the electrical view of a motor – so the angle within on electrical period of the hall-sensors or the voltages. In motors having more than one pole pair, there is a multiple of electrical periods per mechanical turn.
Speed Controller	The FAULHABER controllers used for pure speed control of a motor
Motion Controller	The FAULHABER controllers used for the servo-drive applications
B	FAULHABER BLDC B motors family
BX4	FAULHABER BX4 motors family
BP4	FALUHABER BP4 motors family
BXT	FAULHABER flat BLDC motors family

Description

General Information

For a standard 3 phase BLDC motors, the sensors generate three square wave signals (Hall_A, Hall_B, Hall_C) with a

Speed Controller	Motion Controller V3.0
SC 1801	MC 5004
SC 2402	MC 5005
SC 2804	MC 5010
SC 5004	
SC 5008	

duty cycle of 180° each shifted with 120°. These results in a switching pattern of three digital signals which generate a unique sequence code for every 60°. In other words, the three sensor signals can give a rotor position with a resolution of 60° electrical. For the multi-pole motors, the electrical revolutions per one mechanical revolution are multiple of pole pairs.

The purpose of trapezoidal-commutation is to energize the stator phase windings in a certain sequence. The torque production is caused by the attraction and repulsion between stator field and permanent magnets of the rotor.




Figure 1 Digital hall sensors

Electrical characteristics of the hall sensors of FAULHABER BLDC motors

BLDC motor family	B motors			
BLDC motor types	0620...B 1218...B 1226...B	2057...B(A)	1628...B 2036...B, 2444...B 3056...B, 3564...B 4490B(S)	0824...B 1028...B 1645...BHS 1660 BHS(T)
Supply voltage range [V] min. / typ. / max.	/ - /	3.5 / - / 24	4.5 / - / 24	4.5 / 5 / 5.5
Current consumption [mA] min. / typ. / max.	<i>On request</i>	- / 9 / 15	- / 24 / 35	- / 16 / 23
Max. output current per channel [mA]		40	20	4
Output stage type		Open-drain	Open-collector	Push-pull
Typical external pull up resistor [kΩ], when using a 5V supply		1 ... 5		not required
Reverse polarity protection		-	<input checked="" type="checkbox"/>	-
Number of pole-pairs	1			

Table 3 Electrical characteristics of digital hall sensors in FAULHABER 1 pole-pair BLDC motors

BLDC motor family	BX4 motors with IE3 encoder and digital hall	BX4 motors with digital hall, only	BP4 motors	Flat motors
-------------------	--	------------------------------------	------------	-------------

BLDC motor types	2232...BX4 (S) 2250...BX4 (S) 3242...BX4 3268...BX4	2232...BX4 (S) 2250...BX4 (S) 3242...BX4 3268...BX4	2264...BP4 3274...BP4	1509...B 1515...B 2610...B 2622...B	2214...BXTR(H) 3216...BXTR(H) 4221...BXTR(H)
Supply voltage range [V] min. / typ. / max.	4.5 / 5 / 5.5	2.2 / - / 18	2.7 / - / 24	2.2 / - / 20	2.7 / - / 24
Current consumption [mA] min. / typ. / max.	- / 16 / 23	4.5 / 9 / 15	4.5 / 9 / 14	- / 6 / 12	4.5 / 9 / 14
Max. output current per channel [mA]	4	40	40	25	40
Output stage type	Push-pull	Open-drain			
Typical external pull up resistor [kΩ], when using a 5V supply	not required	1 ... 5			
Reverse polarity protection	-	-	<input checked="" type="checkbox"/>	-	<input checked="" type="checkbox"/>
Number of pole-pairs	2		2	2	7

Table 4 Electrical characteristics of digital hall-sensors in FAULHABER 2 and 7 pole-pair BLDC motors

Pull-up resistor

When the digital hall sensors are using an open drain or open collector output stage, pull up resistors are required. The pull-up resistors (R_{PU}) are simple fixed-value resistors connected between the output terminal and supply voltage terminal of the hall sensor.




Figure 2 Digital hall sensor with pull-up resistor interfaced to controller

A rule of thumb is to use a resistor that is at least 10 times smaller than the value of the input pin impedance of the motor controller. In bipolar logic families which operate at 5 V, the typical pull-up resistor value is 1 kΩ to 5 kΩ. The FAULHABER speed controllers use typically 2 kΩ as the integrated pull-up resistors, therefore drawing typically 2.5mA through the sensor output pin.

Specification of digital hall signals

The general electrical signals of digital hall-sensors are specified as below:

	minimum	nominal	maximum
Phase-to-Phase offset (°e)	112	120	128
Duty cycle (%)	45	50	55
Step angle S (°m) - B motor family	50	60	70
Step angle S (°m) - BX4, BP4 motor family	20	30	40
Step angle S (°m) - BXT motor family	5.6	8.6	11.6

Table 5 Signal specification of digital hall sensors in FAULHABER motors




Figure 3 Example of digital Hall signal

Trapezoidal commutation of BLDC motors with FAULHABER controllers

The following Table-6 gives the details of the motor phases switching sequence for a given hall signal pattern to rotate in clockwise and in counterclockwise direction. The switching states „1“ and „0“ represent the high and low logic level of the digital hall sensors respectively.

Depending upon the hall states (Hall A, Hall B, Hall C), the voltage across the motor phases changes accordingly. For instance, in the Hall state 1-0-1 in clockwise direction, the path of the current begins at the positive pin of the voltage source, flows through the phase A and B of motor windings, finally to the ground pin. At that instance, the motor phase C is remains open (marked with ‘-’ sign in Table-6).

Hallsignals			Motor Phases			Commutation States
Hall A	Hall B	Hall C	MotA	MotB	MotC	
Clockwise Direction (CW)						
0	0	1	-	GND	U _{mot}	6
0	1	1	GND	-	U _{mot}	5
0	1	0	GND	U _{mot}	-	4
1	1	0	-	U _{mot}	GND	3
1	0	0	U _{mot}	-	GND	2
1	0	1	U _{mot}	GND	-	1
Counterclockwise Direction (CCW)						
0	1	0	U _{mot}	GND		1
0	1	1	U _{mot}		GND	2
0	0	1	-	U _{mot}	GND	3
1	0	1	GND	U _{mot}		4
1	0	0	GND		U _{mot}	5
1	1	0	-	GND	U _{mot}	6

Table 6 Trapezoidal commutation excitation sequence with digital hall sensors

Figure 4, shows the signal characteristics of a BLDC motor over one electrical revolution. The hall signals (A, B,C) along with the phase voltages (A,B,C) reflect the clockwise sequence mentioned in the table-6. The motor winding's back-EMF (A-B, B-C, C-A) is added here to show that they are phase shifted by 60°e compared to the corresponding hall signals. This relationship and the excitation sequence are applicable to all the FAULHABER motor families with a digital hall sensor interface.

For multi-pole BLDC motors families, the electrical resolution per one mechanical revolution is as multiple of pole pairs. For instance, a BXT motor with 7 pole-pairs requires 7 electrical revolutions in one mechanical revolution.




Figure 4 Phase voltage, Back-EMF and Hall sensor signals for one electrical revolution (cw)

Rechtliche Hinweise

Urheberrechte. Alle Rechte vorbehalten. Ohne vorherige ausdrückliche schriftliche Zustimmung der Dr. Fritz Faulhaber & Co. KG darf diese Application Note oder Teile dieser unabhängig von dem Zweck insbesondere nicht vervielfältigt, reproduziert, gespeichert (z.B. in einem Informationssystem) oder be- oder verarbeitet werden.

Gewerbliche Schutzrechte. Mit der Veröffentlichung, Übergabe/Übersendung oder sonstigen Zur-Verfügung-Stellung dieser Application Note werden weder ausdrücklich noch konkludent Rechte an gewerblichen Schutzrechten, übertragen noch Nutzungsrechte oder sonstige Rechte an diesen eingeräumt. Dies gilt insbesondere für gewerbliche Schutzrechte, die mittelbar oder unmittelbar den beschriebenen Anwendungen und/oder Funktionen dieser Application Note zugrunde liegen oder mit diesen in Zusammenhang stehen.

Kein Vertragsbestandteil; Unverbindlichkeit der Application Note. Die Application Note ist nicht Vertragsbestandteil von Verträgen, die die Dr. Fritz Faulhaber GmbH & Co. KG abschließt, und der Inhalt der Application Note stellt auch keine Beschaffenheitsangabe für Vertragsprodukte dar, soweit in den jeweiligen Verträgen nicht ausdrücklich etwas anderes vereinbart ist. Die Application Note beschreibt unverbindlich ein mögliches Anwendungsbeispiel. Die Dr. Fritz Faulhaber GmbH & Co. KG übernimmt insbesondere keine Gewährleistung oder Garantie dafür und steht auch insbesondere nicht dafür ein, dass die in der Application Note illustrierten Abläufe und Funktionen stets wie beschrieben aus- und durchgeführt werden können und dass die in der Application Note beschriebenen Abläufe und Funktionen in anderen Zusammenhängen und Umgebungen ohne zusätzliche Tests oder Modifikationen mit demselben Ergebnis umgesetzt werden können. Der Kunde und ein sonstiger Anwender müssen sich jeweils im Einzelfall vor Vertragsabschluss informieren, ob die Abläufe und Funktionen in ihrem Bereich anwendbar und umsetzbar sind.

Keine Haftung. Die Dr. Fritz Faulhaber GmbH & Co. KG weist darauf hin, dass aufgrund der Unverbindlichkeit der Application Note keine Haftung für Schäden übernommen wird, die auf die Application Note und deren Anwendung durch den Kunden oder sonstigen Anwender zurückgehen. Insbesondere können aus dieser Application Note und deren Anwendung keine Ansprüche aufgrund von Verletzungen von Schutzrechten Dritter, aufgrund von Mängeln oder sonstigen Problemen gegenüber der Dr. Fritz Faulhaber GmbH & Co. KG hergeleitet werden.

Änderungen der Application Note. Änderungen der Application Note sind vorbehalten. Die jeweils aktuelle Version dieser Application Note erhalten Sie von Dr. Fritz Faulhaber GmbH & Co. KG unter der Telefonnummer +49 7031 638 345 oder per Mail von mcsupport@faulhaber.de.

Legal notices

Copyrights. All rights reserved. This Application Note and parts thereof may in particular not be copied, reproduced, saved (e.g. in an information system), altered or processed in any way irrespective of the purpose without the express prior written consent of Dr. Fritz Faulhaber & Co. KG.

Industrial property rights. In publishing, handing over/dispatching or otherwise making available this Application Note Dr. Fritz Faulhaber & Co. KG does not expressly or implicitly grant any rights in industrial property rights nor does it transfer rights of use or other rights in such industrial property rights. This applies in particular to industrial property rights on which the applications and/or functions of this Application Note are directly or indirectly based or with which they are connected.

No part of contract; non-binding character of the Application Note. The Application Note is not a constituent part of contracts concluded by Dr. Fritz Faulhaber & Co. KG and the content of the Application Note does

not constitute any contractual quality statement for products, unless expressly set out otherwise in the respective contracts. The Application Note is a non-binding description of a possible application. In particular Dr. Fritz Faulhaber & Co. KG does not warrant or guarantee and also makes no representation that the processes and functions illustrated in the Application Note can always be executed and implemented as described and that they can be used in other contexts and environments with the same result without additional tests or modifications. The customer and any user must inform themselves in each case before concluding a contract concerning a product whether the processes and functions are applicable and can be implemented in their scope and environment.

No liability. Owing to the non-binding character of the Application Note Dr. Fritz Faulhaber & Co. KG will not accept any liability for losses arising from its application by customers and other users. In particular, this Application Note and its use cannot give rise to any claims based on infringements of industrial property rights of third parties, due to defects or other problems as against Dr. Fritz Faulhaber GmbH & Co. KG.

Amendments to the Application Note. Dr. Fritz Faulhaber & Co. KG reserves the right to amend Application Notes. The current version of this Application Note may be obtained from Dr. Fritz Faulhaber & Co. KG by calling +49 7031 638 345 or sending an e-mail to mcsupport@faulhaber.de.