

NEW

Planetary Gearheads

Low Noise, up to -10 dB

6,5 Nm

11 000 min⁻¹

Series 32GPT LN

Values at 22°C

Number of gear stages		2	3	4	4
Reduction ratio ¹⁾		14:1	41:1	178:1	711:1
(rounded)		16:1	49:1	215:1	1 042:1
		20:1	59:1	267:1	1 294:1
		24:1	72:1	323:1	
		30:1	89:1	401:1	
		44:1	108:1	474:1	
			131:1	588:1	
			158:1	862:1	
			196:1		
Continuous torque, max.	Nm	2,3	4	6,5	6
Intermittent torque, max.	Nm	2,9	5,2	8	7,2
Peak torque	Nm	3,5	9	12	10
Continuous input speed, max.	min ⁻¹	10 000	11 000	11 000	11 000
Intermittent input speed, max.	min ⁻¹	12 500	14 000	14 000	14 000
Continuous output power, max.	W	21	14	12	12
Intermittent output power, max.	W	30	20	15	15
Efficiency, max.	%	84	82	65	65
Input inertia with pinion, max.	gmm ²	124	125	58	50
Torsional stiffness, typical	Nm/°	14	14	14	14
Backlash, at no-load, typical	°	0,6	0,6	0,6	0,6
Shaft load, max.:					
– radial (10 mm from mounting face)	N	180	220	300	300
– axial	N	150	180	250	250
Shaft press fit force, max.	N	250	250	250	250
Shaft play:					
– radial (10 mm from mounting face)	mm	≤ 0,07	≤ 0,07	≤ 0,07	≤ 0,07
– axial	mm	= 0	= 0	= 0	= 0
Length without motor L2	mm	34,7	43,1	51,5	51,5
Mass without motor and flange	g	151	194	235	235
Noise reduction level	dB	up to -10 dB (compared to standard 32GPT version)			
Operating temperature range	°C	-30 ... +110			
Direction of rotation, drive to output		=			
Housing material		stainless steel			
Geartrain material		plastic/stainless steel			
Bearings on output shaft		ball bearings, preloaded			


¹⁾ The reduction ratios are rounded, the exact values are available on request or at www.faulhaber.com.

Note: These gearheads are available only with motors mounted.


Note:

The display shows the range of possible operation points of the drives at a given ambient temperature of 22°C.

The diagram indicates the recommended output speed in relation to the available torque at the output shaft.



Dimensional drawing



Options

Example product designation: **32GPT LN 24:1 KS3KL1**

Option	Type	Description
KS1	Output shaft	Round plain shaft, L3 = 21 mm
KS2	Output shaft	Longer round plain shaft, L3 = 31 mm
KS3	Output shaft	Shaft with double flat shape of 12 mm length on opposite sides, L3 = 21 mm
KS4	Output shaft	Shaft with DIN 6885-A keyway and mating key with dimensions 2x2x12 mm, L3 = 21 mm
KS6	Output shaft	Shaft with 12 mm single flat shape and 2 mm cross bore at 6 mm of shaft end, L3 = 21 mm
KS7	Output shaft	Shaft with 12 mm single flat shape and M4 axial threaded hole, L3 = 21 mm
KS8	Output shaft	Shaft with fork shape of 3 mm width opening, L3 = 21 mm
KS9	Output shaft	Shaft with KS4 option and with M4 axial threaded hole, L3 = 21 mm
KR1	Output shaft/flange	Shaft diameter 6 mm with flat shape 15 mm length and 4x M3 threads on flange, L3 = 20 mm (compatible with 32A)
KP1	Ingress Protection	Gearhead with IP54 ingress protection rating (to be combined with specific protected motor)
KL1	Ambient conditions	Low temperature range of -55°C ... +100°C
KC1	Cable orientation	Motor cable/wires or terminals oriented at 15° CCW vs gearhead front threads
KC2	Cable orientation	Motor cable/wires or terminals oriented at 30° CCW vs gearhead front threads

Note: Specified values may differ from the standard values depending on the option. Please consult your sales representative for further information.

Product combination

Number of gear stages	2	3	4
L2 [mm] = length without motor	34,7	43,1	51,5
L1 [mm] = length with motor	76,7	85,1	93,5
2642X...CR/CXR	91,7	100,1	108,5
2657X...CR/CXR	102,7	111,1	119,5
2668X...CR	76,7	85,1	93,5
3242X...CR	91,7	100,1	108,5
3257X...CR	106,7	115,1	123,5
3272X...CR	86,5	94,9	103,3
2250X...BX4	78,9	87,3	95,7
3242X...BX4	104,9	113,3	121,7
3268X...BX4	98,7	107,1	115,5
2264X...BP4	112,8	121,2	129,6
3274X...BP4	90,7	99,1	107,5
3056X...B	98,7	107,1	115,5
3564X...B	51,5	59,9	68,3
3216X...BXTH	50,7	59,1	67,5
3216X...BXTR	76,7	85,1	93,5
AM3248...10			